

SMART DSS TECHNOLOGIES FOR SUSTAINABLE IRRIGATION MANAGEMENT

Mladen Todorović CIHEAM – Mediterranean Agronomic Institute of Bari, Italy mladen@iamb.it

> CLIMASOUTH Training course LARI, Tal Amara, 12-16 December 2016

Integrating and automating ... a complex ADSS at farm and district scale



HYDROTECH architecture

Hydro-Tech - BLULEAF: main features

- Combines soil/crop water status monitoring and soil water balance modeling
- Multi ETo model (depending on data availability)
- "Adjustable" K_Rs and Rs_measured, Kc to local conditions
- Multi crop development model (days/heat units) with adjustable number of development stages
- Multi "Crop response to Water" model and yield prediction (Stewart+Rao)
- Weather forecasting use in DSS
- Separate crop development and water management phases/thresholds (RDI)
- Completely/partially automated (level of automation managed by user)
- Real time remote control and management
- Multi plot/crop management ... Multi-scale (field, farm, irrigation district)
- Water management optimization for dynamic management strategies for different crops/fields
- On field/crop specific management strategies (priorities water / yield / energy / profit ..., inclusion/exclusion of irrigation days/time, etc.)
- Eco-efficiency considered
- Improvable permits insert of new/additional sensors/modules

Main calculation modules and databases of the irrigation scheduling model







Kc corrections

Correction of the Kc values in relation to local climate and crop characteristics

 $Kc_{mid/end} = Kc_{tab} + [0.04(u_2 - 2) - 0.004(RH_{min} - 45)](h/3)^{0.3}$

Correction based upon the fraction of ground covered by vegetation and its height

$$K_{d} = \min\left(1, M_{L}f_{eff}, f_{eff}^{(1/_{1+h})}\right)$$
 Allen and Pereira, 2009



Hydro-Tech: Data Flow Scheme



Geographical location of selected experimental farms together with some representative pictures of different cropping system.



table grape

In the map, the symbols refer to the network of the stations of the regional agro-meteorological service.

Examples of field units for data acquisition



Weather and soil sensors connected to wireless radio dataloggers (Decagon and DyrectaLab devices, Villa Castelli – BR, wine grape)



Soil moisture monitoring with 'capacitance' sensors



ECH2O Decagon sensors

DeltaT PR2 probe

schematic representation of the soil moisture content at the shallow (S) and deeper (D) sensor position, respectively (from Fereres et al., 2012)

Examples of field units and remote control of water supply network







Hydrants and pumps monitoring and control with wireless radio dataloggers (ETG devices, IAMB, Valenzano – BA, pumping station and hydrant network)





Examples of remote control of electrovalves and pumps at a private farm









Examples of 'web' applications at district scale



Examples of 'web' applications at farms scale



Examples of 'web' applications at field scale

~

	💁 📃 Angelo Abbracciavento 🗸	
Dashboard	AB-4	
AB-1		
Ø AB-2	Bilancio Registro trattamenti Dati meteo Dati suolo Parametri biosistema Strategia irrigua	
AB-4	🖉 Strategia consigliata	
AB1-Doppia ~	Testo di prova	
AB1-Singola ~		Current status and
Guida in linea ~	99% 96% 92% 86% 82% 1 21-11-2013 1 21-11-2013 1 22-11-2013 1 23-11-2013 1 24-11-2013	projected 3-days changes in the percentage of soil water content, with the
	Infografiche	seasonal trend of ETo versus ETc and the seasonal trend of soil water depletion
	PAW TAW Depletion TAW Depletion TA	

2013 © Quadro sinottico.

Example of MOBILE Android application









HydroTech DSS

Examples of mobile Android applications





Allegagione

Personal settings: Start date: 19/06/2013









(Mesagne – BR, wine grape, loamy soil, depth 0.80 m)

Sensitivity to water stress in different phenological stages



Main peach phenological stages and corresponding trend of the soil water depletion in the root zone adopting a regulated deficit irrigation with variable MAD









flowering		pit hardening vegetative development				fruit development			hai	vesting		post-harvest			
	5	tage I			5	tage II				stag	e III			stag	e IV
22/3	6/4	21/4	<mark>6/5</mark>	21/5	5/6	20/6	<mark>5/1</mark>	20/7	4/8	19/8	3/9	18/9	3/10	8/10	2/11



Cumulated irrigation volumes applied to peach orchard



Conclusions

- 2 years of experimental/testing activity provided the field evidence of strengths and weaknesses of the system.
- HT-DSS considered the eco-efficiency aspects of water management (economic benefits vs. resources use).
- **Product quality** in relation to water regime seems to be of higher relevance (wine grapes).
- HT-DSS integrates the scientific knowledge with the local experience: the best way to design DSS according to the farmer's perspectives.
- The results of testing indicated the satisfaction of the farmers who emphasized the saving of water, energy and time (dedicated to water management), economic benefits and eco-efficiency increase.
- This has confirmed that the support tools and DSS for agricultural water management are effectively required by farmers, technicians and decision makers.



LAND and WATER Dept.

www.cihea

www.ciheam.org www.iamb.it mladen@iamb.it

www.blueleaf.it

http://cloud.blueleaf.it/dashboard/main.html

Many thanks for your attention

Hydro-Tech team:

and hover

Erminio Riezzo, Mario Zippitelli, Sysman srl., Mesagne, Rome, Italy Vito Buono, CIHEAM – Mediterranean Agronomic Institute of Bari, Italy Vito Cantore, Francesca Boari, CNR, Institute for Crop Production, Bari, Italy